

DRAINLINES TO MAINLINES

EVERYTHING YOU NEED TO UNCLOG ALL DRAIN AND SEWER LINES



Model C (3"- 10" lines up to 200')

- Direct cable drive off front of machine allows 500 RPM cable rotation (twice that of drum machines) and distances over 200'
- Enclosed 1/2 H.P. capacitor motor with custom-built gear mechanism gives you longer life and plenty of drain and sewer cleaning power
- Weighs only 75 lbs. for easy handling and transporting
- Folding handle makes for compact storage and allows use in crawl spaces
- Unique carry handle for balance and easy handling
- Adjustable clutch protects machine and cable from overload in tough stoppages and gives operator more power at the turn of a screw



Model D-5 (3"- 10" lines up to 100')

- High density polyethylene drum and belt guard will not rust or dent
- 3 sealed heavy-duty ball bearings, support for drum and thick wall guide tube for extended wear
- Large 10" solid wheels for stabilization of unit while in operation
- Heavy-duty, 1/2 H.P. capacitor type motor produces more torque and plenty of power
- 5 position height adjustment on handle
- Continuous belt skids and wheel on handle for safe and easy loading
- Quick remove continuous cable feeder and drum



Model Z5-P-AF

(1 1/4"- 3" lines up to 75')

- 2-Way auto cable feed advances and retrieves cable with the push of a lever (manual cable feed also available)
- Cable guide spring keeps hands off rotating cable for added safety and better handling
- Runs up to 75' of 1/2" diameter cable
- Built-in drum shaft slip clutch
- Rugged 1/3 H.P. motor
- Upright frame with 10" wheels and folding handle
- Wheel brake stabilizes unit while in operation
- Unique inner drum eliminates cable tangling in drum
- 20 Ft. power cord with GFCI



Model E (1 1/4"- 3" lines up to 75')

- Built-in drum shaft slip clutch
- Unique inner drum design eliminates cable buckling
- Rear bar to shield motor and allow for two position operation
- Epoxy powder coated drum helps deter corrosion
- Rugged 1/3 H.P. motor
- Heavy-duty steel tubular frame
- Built-in GFCI on a 20' line cord protects operator from electrical shock. Cord wraps for easier transport
- Runs up to 75' of 3/8" or 1/2" diameter certified music wire cable with *genuine* galvanized aircraft wire inner core



Model N (1 1/4"- 3" lines up to 100')

- Runs up to 75' of self-feeding Dualmatic cable in low-maintenance 5' sections
- Rugged 1/3 H.P. motor with built-in safety clutch
- Cast aluminum inner drum and cable guide to eliminate tangling in the drum
- Drum removes quickly and easily
- Convenient foot operating switch
- Built-in GFCI on a 20' line cord protects operator from electrical shock
- Optional 2-wheel cart for easy transport



Model CT (3/4"- 2 1/2" lines up to 50')

- Unique variable speed motor control gives operator maximum cable control and exceptional cleaning power from 75 to 350 RPM with constant torque
- Powerful and quiet 1/5 HP, 90 Volt DC motor
- Standard unit features a hand tighten Jacobs Chuck. Also available with a 2-way auto cable feed that keeps hands off rotating cable as it advances and retrieves cable with the push of a lever
- Cable guide hose eliminates cable whipping and helps keep work area clean
- Stainless steel cable drum will not rust, resists denting
- Two position vertical upright or horizontal operation
- Built-in GFCI on 20' line cord protects operator from electrical shock
- Runs 1/4", 5/16", and 3/8" cable



Upright Position



Model 325 (4"- 14" lines up to 500')

- Direct drive of self-feeding cable
- Rugged steel base and heavy-duty clutch withstand rough use
- Pneumatic roller bearing wheels maneuver over all types of terrain
- Conveniently located foot-operated automotive clutch pedal
- Removable handle and retractable gear shift allow compact storage
- 6.5 H.P., 4-cycle IC Briggs and Stratton engine with recoil starter
- A 3-speed/reverse transmission with automotive-type Rockford clutch
- Contractor and municipal use



Model 800 (4"- 24" lines up to 650')

- Infinitely variable drive speed system
- 8 H.P. gas or 9 H.P. diesel engine
- Runs up to 650'
- Hydrostatic transmission
- Safety clutch for cable overload protection
- Uses 8" heavy-duty municipal dual cable
- Removable handle for compact storage and transport
- High pressure hose rated up to 3000 PSI
- Ideal for contractors and municipalities
- Optional cable reel
- Wide variety of cleaning tools available
- 10" pneumatic tires for easy maneuverability
- Portable and powerful
- Contractor and municipal use



Model S (1 1/4"- 2 1/2" lines up to 35')

- Commercial grade 1/2" heavy-duty drill
- Double insulated drill for shock protection
- Compact and lightweight
- Lightweight stainless steel cable drum won't rust, break or crack
- Cast aluminum hand guard is designed for safety and ease-of-use
- Hand-tighten cable chuck
- Expanded end or drop head cable in 15', 25', 35' lengths



Model K (1 1/4"- 3" lines up to 100')

- Easy to use hand operation
- Runs up to 100'
- Powder coated steel cable cage rotates freely
- Self-aligning bearings
- Thumbscrew locks cable at front of cage
- Comes with 1/2" diameter monowire cable or 1/2" aircraft wire reinforced inner core cable

For More Information, Call 800-833-1212 or Visit Our Web Site at www.electriceel.com

Note: Always refer to operator's manual and safety instructions before operating any drain and sewer cleaning equipment.

ELECTRIC EEL MANUFACTURING CO., INC.
501 W. Leffel Lane, Springfield, Ohio 45506
937-323-4644 Toll-Free: 800-833-1212 FAX: 937-323-3767
E-mail: info@electriceel.com www.electriceel.com



Electric Eel®

DRAIN CLEANING TOOLS FOR PROFESSIONALS

HIGH PRESSURE ELECTRIC & GAS EEL JET JETTERS




EJ1500

- Cleans 1½"–4" dia. drain lines • 1500 PSI / 1.7 GPM • 1.5 H.P., 15 AMP motor
- Duplex pump w/pulsation • Reel capacity 150' of 1/4" hose • Pump/motor assembly removes in seconds for added portability
- Sturdy 10" pneumatic tires for ease of transport • Thermal relief valve and inlet shut off valve • Removable handle/reel on cart assembly • Utilizes 1/8" and 1/4" dia. jet hose • 20' power cord w/GFCI.



EJ3000

- Cleans 2"–8" dia. lines up to 300' • 13 HP overhead valve engine for smooth quiet running and dependable operation – **Electric Start Available**
- 2-to-1 gear reduced triplex pump with pulsation for longer life • 300' Capacity Hose Reel • 12" pneumatic tires for easy maneuverability on rugged steel base with front bar for motor protection
- Heat shield to protect hose • Convenient nozzle storage on unit • Throttle back control automatically adjusts engine speed • Low tone muffler for quiet operation • Utilizes 1/4" and 3/8" dia. jet hose.



Sludge. Ice. Grease. Sand. Soap. Dirt. Debris. Whatever the problem, Electric Eel steel nozzles will penetrate and clean tough problems from pipe walls with a variety of spray angles.

PIPELINE INSPECTION SYSTEMS



< All eCAM units have a built-in Battery Cradle* (Battery Not Included)

*Accepts a Milwaukee M18 battery. Allows easy access to power for remote field work or where electricity is not available. Battery life is 6-7 hours.



eCAM pro2

Features

- Rugged stainless steel housed 1.68" dia. self-leveling color camera
- 12.1" Daylight readable display
- 8" wheels for easy transport and maneuverability
- Built-in Battery Cradle

Camera

- Rugged stainless steel housed 1.68" dia. self-leveling color camera with sapphire lens, 20 LED light ring and high resolution CCD element
- Flexible camera spring designed to navigate 3" P-traps
- Auto iris adjusts lighting automatically
- Impact-resistant polycarbonate light ring cover
- Industry standard 512HZ sonde

Reel & Frame

- Standard with 200 ft. of braided Fiberglass Premium ½" dia. push rod (reel capacity available up to 400 ft.)
- Secure-locking reel brake
- Rugged powder-coated steel tube and bar construction
- 8" wheels for easy transport and maneuverability

Monitor

- Audio/Video out jacks
- 12.1" Daylight readable display
- Record directly to USB flash drive
- Click touch controls and 1-touch recording
- 16 pages of text writing with memory saves
- On screen footage counter
- Adjustable light controls
- Voice over recording (built-in)
- Rename files on flash drive after recorded
- 512 Hz sonde
- 8X Zoom function



Inspects 3"-10" Lines



eCAM ace2SL

Features

- Self-Leveling color camera
- One-Touch USB recording
- On-screen footage counter
- Wheels for easy transport and maneuverability



Self-Leveling Color Camera Standard on the Ace 2 SL

eCAM acewifi

Features

- WiFi enables users to record video with their mobile device
- Custom downloaded APP enables user to see video
- Wheels for easy transport and maneuverability



Optional Self-Leveling Color Camera Available for the Ace WiFi & Ace

eCAM ace

Features

- Stainless steel housed 1.68" dia. color camera
- 200' of braided fiberglass premium ½" dia. push rod
- Wheels for easy transport and maneuverability



Standard Features and Specifications for eCAM ACE 2 SL, eCAM ACE WiFi & eCAM ACE Pipeline Inspection Systems Include:

Camera • Rugged stainless steel housed 1.68" dia. color camera with sapphire lens, 20 LED light ring and high resolution CCD element (optional self-leveling color camera available) • Flexible camera spring designed to navigate 3" P-traps • Auto iris adjusts lighting automatically • Industry standard 512HZ sonde • Impact-resistant polycarbonate light ring cover • Camera options: .875" dia. color camera for inspecting 1½"–3" lines; 1.23" dia. color camera for inspecting 2"–4" lines.

Monitor • 5.4" LCD monitor with AR film for optimal viewing in sunlight encased in an anodized aluminum housing mounted to the reel • Protective acrylic, anti-glare monitor shield • Video output jack for recording option.

Reel & Frame • Rugged and portable powder-coated steel frame • Standard with 200 ft. of braided Fiberglass Premium ½" dia. push rod • Secure-locking reel brake • Heavy-duty screen cover closes to protect the monitor when in transit or storage, flips up as a sun shield and can be retrofitted to existing units.



LF2000

Digital receiver locates 512Hz sondes in cast iron and non-metallic lines

eCAM ace100-micro

Features (((WiFi)))

- Video is streamed directly to any mobile device which can be used as your monitor
- Easy to Use WiFi App
- Compact & portable
- Save files on your device; transfer via Email, Text, Cloud
- Inspects 1½"–3" dia. pipes up to 100 ft.
- Weighs only 15 lbs.
- 512HZ sonde
- 1" diameter camera head • 100 ft. of .271" diameter push rod • Resettable footage counter displays feet and meters
- Single Button WiFi Hub



XT-512 Locator

Locates eCam pipeline inspection cameras 512Hz sondes



Closest Auger

- 3' music wire cable for greater flexibility
- Heavy-duty zinc plated construction
- Protective tubing helps prevent marring of toilet bowl

Handle (1"-2½" lines up to 35')

- Opens clogged sinks, lavatories, bathtubs and shower stall drains
- Heavy-duty steel drum holds up to 35' cable
- Runs ¼" and 5/16" diameter cable
- Convenient thumb screw locks cable securely



Cables for every need

- Self-feed **Dual Cables** for 3"-10" lines available in regular, heavy-duty and municipal
- **J Cables** with dual cable benefits for 2"-4" lines
- **Tri-Max** ¾" or 5/8" cable with slot or keyhole end fittings to fit most drain cleaning machines
- ½" **Aircraft Wire Reinforced Cables** with front & rear fittings (available in **No Core**)
- **Aircraft Wire Reinforced Cables** (5/16" and 3/8") for use with Drop Head series tools
- **Expanded End Aircraft Wire Reinforced Cables** with bulb end & no rear fittings (5/16", 3/8")
- **Expanded End Cables** to negotiate pipe traps & drain cross bars (¼", 5/16", 3/8")

Note: Always refer to operator's manual and safety instructions before operating any drain and sewer cleaning equipment.

ELECTRIC EEL MANUFACTURING CO., INC.
501 W. Leffel Lane, Springfield, Ohio 45506
937-323-4644 Toll-Free: 800-833-1212 FAX: 937-323-3767
E-mail: info@electriceel.com www.electriceel.com 7/21 LT-10



Electric Eel

DRAIN CLEANING TOOLS FOR PROFESSIONALS